

SUPER SEAL AGGREGATE CONCRETE CRACK FILLER

With Brown Specked River Sand to match the texture, color, and overall appearance of
Aggregate (Brown) Concrete

Bottle: 1 Quart (946 ml) Net Weight 4 lbs (1.8 kg) Settling will occur.

NOTE: Liquid bonding agent will dry clear. Layer Crack Filler at depths of no more than a ¼" at a time. Temperature must be above 50° F. In cool weather, separation can occur. For best results, seal aggregate concrete with SUPER SEAL 30 Brown Tint or Clear after crack filler has dried.

DIRECTIONS:

1. Clean concrete well. Power washer will restore appearance.
2. Allow concrete to dry.
3. **SHAKE WELL!** Continue to shake well throughout application. Once opened, secure top while shaking. Shake upside down.
4. Snip spout on cap to desired width of pour.
5. Pour crack filler into crack. Tamp excess into crack, if necessary.
6. Allow filler to dry before sealing. In warmer temperatures it will dry faster than in cooler temperatures.
7. Seal with Super Seal 30 Brown Tint or Clear to protect and beautify concrete.

DISCLAIMER: Manufacturer warrants the product to be free from defects and will replace or refund the purchase price of said products proven defective. Since the manufacturer has no control over handling, use, or storage; no guarantee express or implied is offered. The suitability of the product for any use shall be solely up to the user. Manufacturer retains right to legal venue.

PATENT PENDING

Made in USA by:

CLEMONS CONCRETE COATINGS

505 Cave Road ★Nashville, TN 37210★(615) 872-9099★www.ccc-usa.com