



CLEMONS CONCRETE COATINGS

Solid Color **SUPER SEALER STAINS** for Concrete



WHITE



ANTIQUE WHITE



HARVEST



PEACH



FIESTA



ADOBE BUFF



SUN BUFF



SAND BUFF



SANDSTONE



MAPLE



COOL WHITE



DESERT TAN



AUTUMN



NUTMEG



WALNUT



SABLE



PEWTER



TERRA COTTA



BRICK



TILE RED



STORM GRAY



HAZY BLUE



DARK GRAY



SLATE



CHARCOAL

ABOVE COLORS ARE ALSO AVAILABLE IN SEMI-TRANSPARENT



KHAKI



NEW GRAY



BATTLESHIP

**CURE & SEAL
COLORS**

Colors will vary on each surface. Sample before proceeding.

SUPER SEALER STAINS

PRODUCT DESCRIPTION

SUPER SEALER STAIN is an acrylic resin stain formulated especially for concrete. When applied properly it resists cracking, chipping, peeling and mildew. It dries to a semi-gloss and resists oils, detergents, acids, salts, and other chemicals. It dust-proofs and aids clean-up. SUPER SEALER STAIN is packaged in 1-gallon and 5-gallon containers. SUPER SEALER STAIN is a pure acrylic for longer lasting results on cured concrete. Colors designated CURE & SEAL are styrene acrylic for application to freshly poured concrete. For added protection and depth of gloss, finish with clear TOP COAT.

GENERAL USES

- ★ Fully-cured concrete (use our stains designated as CURE & SEAL for uncured concrete)
- ★ Interior and exterior surfaces (good ventilation and etching of concrete is required for interior applications)
- ★ Broomed/textured finishes
- ★ Smooth-troweled finishes (pre-etching required)

FEATURES

- ★ Penetrates the surface for a good bond
- ★ Quick-drying
- ★ Resistant to most oils and greases
- ★ Water resistant
- ★ Uniform finish appearance
- ★ Seals and protects the surface
- ★ Rejuvenates old concrete
- ★ Hides "undesirable" appearances

SURFACE PREPARATION

Surfaces must be cleaned and degreased prior to application with Clemons CLEANER / DEGREASER. Etch concrete with Clemons ETCH & CLEAN. Rinse thoroughly. Allow a day to dry. Sample a spot before proceeding to ensure color and compatibility are acceptable. Blend multiple containers to ensure consistent color. Concrete should be fully cured for 28 days. Apply SUPER SEALER STAIN to cured concrete.

APPLICATION

Apply the coating with an airless sprayer or roller. Brushes may be used to cut in tight areas. One coat will yield an opaque finish, and two coats will give a glossier, painted look. For a clear glossy finish, apply TOP COAT. For garages and other interior concrete floors, applying SUPER WAX will add slip resistance and protect from scratching.

SLIP RESISTANCE

On any concrete floor, you may add SUPER GRIP non-skid paint additive. Follow directions on non-skid additive and do not overload system. When using a non-skid additive, do not add to first coat. Add it to second coat. All non-skid additives shorten the life of the film to some degree.

CLEAN UP

Clean up tools with an aromatic solvent such as A100 Solvent or Xylene.

COVERAGE RATES

Finish	1st Coat Square Feet.	2nd Coat Square Ft.
Broom swept	200	250
Stamped	200	250
Smooth trowel	250	300
Block	100	150

Note: The concrete's texture and porosity will affect the coverage rates. Therefore, coverage rates are approximate.

LIMITATIONS

- ★ Refer the Material Safety Data Sheet prior to use
- ★ Should not be used on slabs to receive bonded toppings
- ★ Rubber-wheeled tires may leave marks
- ★ Do not over-apply
- ★ Apply only when surface and air temperatures are between 50° F and 90° F.
- ★ Do not use caustic, corrosive, citrus-based, or ammonia detergents to clean the sealed surface
- ★ Gasoline and hot solvents will melt stain. See NOTE below.

TECHNICAL INFORMATION

Solids:	38%	Pounds/Gallon:	8.9
Tack-free @ 73°F, 50% RH:	1 hour	Recoat Time:	3-4 hours
Foot Traffic:	24 hours	Vehicle Traffic:	72 Hours
VOC Content:	<600 g/L	Flashpoint:	105° F
Resin:	Acrylic	Solvent:	Aromatic Hydrocarbon
Finish:	semi-gloss	Color:	As labeled
DOT Information:	Not Regulated <119 gallons		

NOTE: Gasoline and other auto parts cleaners containing hot solvents will melt stain. Wiping will smear stain. Allow to dry. Either leave be for protection or re-coat with stain for best appearance. If floor will be regularly exposed to chemicals, it is highly recommended that you test a spot before proceeding with whole floor.

CAUTION! Contains flammable solvents. Provide adequate ventilation and avoid sparks and open flames. Continue to ventilate after installation until all vapors have been removed. For skin contact, wash affected area with soap and water. For eye contact, flush with water for at least 15 minutes and seek medical attention.

Made in U.S.A.

CLEMONS CONCRETE COATINGS

505 Cave Rd ★ Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052